

SAFETY DATA SHEET

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 05. 06. 2018 Product code: AP7100

Revision: 25. 11. 2019

Replaced version: 05. 06. 2018

Page: 1 z 12

Trade Name: **PP PLASTIC PRIMER**

SECTION 1: Identification of the mixture and the company/undertaking

1.1 Product identifier:

Trade Name: **PP PLASTIC PRIMER**

Mixture description: Solvent coating (aerosol).

1.2 Relevant identified uses of the mixture or mixture and uses advised against:

Identified uses: Paint, surface treatment.

Uses advised against: Recommended for identified uses.

1.3 Details of the supplier of the safety data sheet:

GOX7-EUROPE s.r.o.

Chlumčanská 396

439 02 Cítoliby,

Czech republic

Tel.:+420 777 691 661

competent person responsible for MSDS: info@gox7.cz

1.4 Emergency telephone number:

112 (General emergency phone).

SECTION 2: Hazards identification

The mixture is classified as dangerous as follows:

2.1 Classification of the mixture:

according to 1272/2008/EC

Aerosol 1; H222, H229
Acute Tox. 4; H312+H332
Eye Irrit. 2; H319
Skin Irrit 2; H315
STOT SE 3; H336
STOT SE 3; H335
STOT RE 2; H373
Aquatic Chronic 3; H412

Full text of H-phrases: see section 16.

The most important adverse physicochemical, human health and environmental effects:

Extremely flammable aerosol. Pressurised container: May burst if heated. Harmful in contact with skin or if inhaled. Causes serious eye and skin irritation. May cause drowsiness or dizziness, respiratory irritation. Repeated exposure may cause skin dryness or cracking. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

2.2 Label elements:

hazard pictograms



SAFETY DATA SHEET

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 05. 06. 2018 Product code: AP7100

Revision: 25. 11. 2019

Replaced version: 05. 06. 2018

Page: 2 z 12

Trade Name: **PP PLASTIC PRIMER**

--	--

SAFETY DATA SHEET

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 05. 06. 2018 Product code: AP7100

Revision: 25. 11. 2019

Replaced version: 05. 06. 2018

Page: 3 z 12

Trade Name: **PP PLASTIC PRIMER**

<i>signal word</i>	Danger.
<i>ingredients of the mixture to be labeled</i>	Contains acetone, xylene, ethyl acetate.
<i>hazard statements</i>	H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H312+H332 Harmful in contact with skin or if inhaled. H319 Causes serious eye irritation. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H335 May cause respiratory irritation. H373 May cause damage to organs through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects.
<i>precautionary statements</i>	P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P403 Store in a well-ventilated place. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P280 Wear protective gloves/protective clothing/eye protection. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 Dispose of contents/container at the site of hazardous waste collection in the village.
<i>supplemental hazard information</i>	EUH066 Repeated exposure may cause skin dryness or cracking. VOC: 95%

2.3 Other hazards:

The mixture meets not the criteria for PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

3.2.1 Substances presenting a health or environmental hazard in the mixture

<i>Chemical identity</i>	<i>CAS</i>	<i>EC-No. Registration No.</i>	<i>Content ** (wt. %)</i>	<i>Classification 1272/2008/EC</i>
--------------------------	------------	--------------------------------	---------------------------	------------------------------------

SAFETY DATA SHEET

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 05. 06. 2018 Product code: AP7100

Revision: 25. 11. 2019

Replaced version: 05. 06. 2018

Page: 4 z 12

Trade Name: **PP PLASTIC PRIMER**

xylylene	1330-20-7	215-535-7 01- 2119488216-32	approx 45	Flam. Liq. 3; H226 Acute Tox. 4; H312+H332 Eye Irrit. 2; H319 Skin Irrit. 2; H315 STOT SE 3; H335 STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412
petroleum gases, liquefied (LPG) *)	68476-85-7	270-704-2 not available	approx 25	Flam. Gas 1; H220 Press. Gas (Liq.); H280
acetone	67-64-1	200-662-2 not available	approx 14	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066
ethyl-acetate	141-78-6	205-500-4 01- 2119475103-46	approx 11	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066
epoxy resin	25068-38-6	500-033-5 not available	0,078	Eye Irrit. 2; H319 Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411

Contains less than 0.1% of 1,3-butadiene (*)); **) see section 16 classification procedure.

3.1.2 Impurities, stabilising aditives, constituents other than the main constituent

<i>Chemical identity</i>	<i>CAS</i>	<i>EC-No. Registration No.</i>	<i>Content (wt. %)</i>	<i>Classification 1272/2008/EC</i>
not identified	---	---	---	---

SECTION 4: First aid measures

Keep the person at physical and mental rest and warm. In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

4.1 Description of first aid measures:

Inhalation:

Move person to fresh air. If breathing stops, apply artificial respiration and seek immediate medical attention. Place unconscious person on the side in the recovery

SAFETY DATA SHEET

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 05. 06. 2018 Product code: AP7100

Revision: 25. 11. 2019

Replaced version: 05. 06. 2018

Page: 5 z 12

Trade Name: **PP PLASTIC PRIMER**

position and ensure breathing can take place.

Skin contact:

Remove contaminated clothing immediately and wash skin with soap and water. Do not use solvents or thinners.

Eye contact:

Flush thoroughly with water. Remove contact lenses if present after the first 5 minutes and continue flushing for several more minutes (least 15 minutes). Get medical attention.

Ingestion:

Unlikely (aerosol). If this nevertheless happens, rinse out mouth with clean water. Do not induce vomiting. Get medical attention immediately. Provide fresh air, warmth and rest, preferably in comfortable upright sitting position.

4.2 Most important symptoms and effects, both acute and delayed:

Overexposure may result in light headedness, staggering gait, dizziness, and possible nausea. May cause severe eye and skin irritation. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible contact dermatitis. Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system.

4.3 Indication of any immediate medical attention and special treatment needed:

Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media:

Suitable extinguishing media:

Use water fog, dry chemical, carbon dioxide or foam.

Extinguishing media which shall not be used for safety reasons:

Solid streams of water may be ineffective. Burning product will float on the surface and spread fire.

5.2 Special hazards arising from the substance:

Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Vapours are heavier than air and may travel along surfaces to remote ignition sources and flash back. Combustion will produce oxides of carbon and hydrocarbons.

5.3 Advice for fire-fighters:

In the event of fire, wear self-contained breathing apparatus and clothing protective against chemicals. Keep extinguishing aerosols away from the danger area, if possible without risk.

SECTION 6: Accidental release measures

SAFETY DATA SHEET

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 05. 06. 2018 Product code: AP7100

Revision: 25. 11. 2019

Replaced version: 05. 06. 2018

Page: 6 z 12

Trade Name: **PP PLASTIC PRIMER**

6.1 Personal precautions, protective equipment and emergency procedures:

Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Use non-sparking tools, avoid electrostatic charge. Other protective measures - see section 7.

6.2 Environmental precautions:

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Do not allow to enter waters or soil. Report spills to authorities as required.

6.3 Methods and material for containment and cleaning up:

Aerosol, mainly local air pollution will occur. If, however, a liquid fraction is leaking, absorb spillage using an absorbent, such as earth, sand or vermiculite. Place in container for disposal according to local regulations (see section 13). Pump off larger quantities. Use non-sparking tools.

Afterwards ventilate area and wash spill site.

6.4 Reference to other sections:

Protective equipment: see section 8. Dispose according to the section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

Provision of very good ventilation in the working area. Vapour/air mixtures are heavier than air. Adequate ventilation at the floor area must be ensured as well. Eye bath required. These locations must be signposted clearly. Keep away from sources of ignition - No smoking. Take measures to prevent the build-up of electrostatic charge. Keep containers tightly sealed. Prevent formation of aerosols. Do not use any tools that cause sparks.

When using, do not eat, drink or smoke. Wash hands with warm water and soap before breaks and after work.

7.2 Conditions for safe storage, including any incompatibilities:

Store in original tightly closed packing in dry and well-ventilated areas. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Recommended storage temperature: 5 - 30 °C. Keep away from direct sunlight.

7.3 Specific end use(s):

In household and industry.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.1.1 Exposure limit value in UK:

LPG:

8 h: 1800 mg/m³ short: 4000 mg/m³

acetone:

8 h: 1210 mg/m³

short: 3620 mg/m³

xylene:

8 h: 220 mg/m³, short: 441 mg/m³

ethyl-acetate:

8 h: 730 mg/m³

short: 1460 mg/m³

SAFETY DATA SHEET

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 05. 06. 2018 Product code: AP7100

Revision: 25. 11. 2019

Replaced version: 05. 06. 2018

Page: 7 z 12

Trade Name: **PP PLASTIC PRIMER**

8.1.2 DNEL:

DNEL, PNEC are not available.

8.2 Exposure controls

8.2.1 Exposure reduction (technical measures):

Where exposure cannot be prevented by other means the use of individual protection measures, such as personal protection equipment is necessary. Ensure adequate ventilation of the workplace. Regularly measure the concentration of this agent in the workplace atmosphere.

8.2.2 Individual protection measures, such as personal protective equipment:

Protective clothing should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of the protective clothing to chemicals should be ascertained with the respective supplier. Workers in the risky process/areas identified should be trained.

<i>Respiratory protection:</i>	Required when vapours/aerosols are generated (recommended filter type A) and where risk assessment shows air-purifying respirators are appropriate use.
<i>Hand protection:</i>	Handle with gloves, e.g. nitril-rubber, strength > 0.55 mm, penetration time > 480 min.; leather is not suitable.
<i>Eye/face protection:</i>	chemical safety goggles
<i>Skin protection:</i>	suitable protective clothing

8.2.3 Environmental exposure reduction:

Uncontrolled escape of substance/formulation into environment is to be avoided.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties:

<i>Appearance (at 20 °C):</i>	aerosol
<i>Colour:</i>	transparent
<i>Odour:</i>	characteristic
<i>Odour threshold:</i>	not available
<i>pH (at 20 °C):</i>	not available
<i>Melting point/freezing point:</i>	not available
<i>Boiling point (range):</i>	not available
<i>Flash point:</i>	< -18 °C (propellant gas)
<i>Evaporation rate:</i>	not available
<i>Flammability:</i>	flammable mixture
<i>Explosive limits</i>	<i>lower: (% vol.)</i> 1,8 (propellant gas) <i>upper: (% vol.)</i> 12,8 (propellant gas)
<i>Vapour pressure: (20 °C)</i>	not available
<i>Vapour density:</i>	not available

SAFETY DATA SHEET

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 05. 06. 2018 Product code: AP7100

Revision: 25. 11. 2019

Replaced version: 05. 06. 2018

Page: 8 z 12

Trade Name: **PP PLASTIC PRIMER**

Relative density:	not available
Solubility in water (20 °C) :	not available
Partition coefficient: n-octanol/water:	not available
Auto-ignition temperature:	not available
Decomposition temperature:	not available
Viscosity:	not available
Explosive properties:	non-explosive
Oxidising properties:	none
9.2 Other information	
not known	

SECTION 10: Stability and reactivity

10.1 Reactivity:

Low reactivity.

10.2 Chemical stability:

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions:

Not known.

10.4 Conditions to avoid:

Heat, flames and sparks. Protect from higher temperatures (over 50 ° C) and direct sunlight, risk of aerosol packaging explosion. Do not use in the presence of a source of ignition.

10.5 Incompatible materials:

Strong oxidizing agents.

10.6 Hazardous decomposition products:

Carbon oxides.

SECTION 11: Toxicological information

11.1 Information on toxicological effects:

Acute toxicity:

- LD_{50} oral, rat ($mg.kg^{-1}$):

ATE_{mixture} > 2000

- LD_{50} skin, rat or rabbit ($mg.kg^{-1}$):

ATE_{mixture} = 1833 (for xylene LD 50 = 12 126 [registration], but in Annex VI is stated H312; therefore, ATE for Acute Tox 4 H312 which is 1100 is used for classification)

- LC_{50} inhalation, rat, gas or vapour ($mg.l$):

ATE_{mixture} > 18.3 (for xylene LC 50 = 27 [registration], but in Annex VI is stated H332; therefore, ATE for Acute Tox 4 H332 which is 11 is used for classification)

Skin corrosion/irritation:

irritant, cat. 2

Serious eye damage/irritation:

irritant, cat. 2

Respiratory or skin sensitisation:

no

SAFETY DATA SHEET

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 05. 06. 2018 Product code: AP7100

Revision: 25. 11. 2019

Replaced version: 05. 06. 2018

Page: 9 z 12

Trade Name: **PP PLASTIC PRIMER**

Germ cell mutagenicity:	no
Carcinogenicity:	no
Reproductive toxicity:	no
STOT-single exposure:	may cause drowsiness or dizziness, respiratory irritation
STOT-repeated exposure:	may cause skin dryness and cracking, may cause damage to CNS
Aspiration hazard:	aerosol, is not classified as such, see section 16
Additional information: not known	

SECTION 12: Ecological information

12.1 Toxicity:

- LC ₅₀ 96 H, fish (mg.l ⁻¹):	no data available
- EC ₅₀ 24 H, daphnia (mg.l ⁻¹):	no data available
- IC ₅₀ 72 H, algae (mg.l ⁻¹):	no data available

12.2 Persistence and degradability: no data available

12.3 Bioaccumulative potential: no data available

12.4 Mobility in soil: no data available

12.5 Results of PBT and vPvB assessment: product is neither a PBT nor a vPvB substance

12.6 Other adverse effects:
no data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods:

Disposal methods of the substance and the contaminated packaging:

Fully use the aerosol. Do not take the unused product into the collection or other disposal. Do not throw into the fire! Dispose of the packaging after full emptying. Never remove it by draining into drains! The waste producer is responsible for sorting waste and disposing of. Potential EU waste-code 08 01 11 for container, 15 01 10 for mixture.

Physical/chemical properties that may affect waste treatment options:

Extremely flammable.

Union provisions relating to waste:

- directive 2008/98/EC

SECTION 14: Transport Information

14.1 UN number: 1950

14.2 UN proper shipping name:

SAFETY DATA SHEET

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 05. 06. 2018 Product code: AP7100

Revision: 25. 11. 2019

Replaced version: 05. 06. 2018

Page: 10 z 12

Trade Name: **PP PLASTIC PRIMER**

- ADR/RID/IMDG/IATA	AEROSOLS, flammable
14.3 Transport hazard class(es):	2
14.4 Packing group:	-
14.5 Environmental hazards:	no
14.6 Special precautions for user:	none
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code:	not available
ADR/RID:	
- classification code	5F
- labels	2.1
- hazard identification code	-
- tunnel restriction code	D
IMDG:	
- EmS	F-D, S-U

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the mixture:

Regulation No. 1907/2006/ES, REACH.

Regulation No. 1272/2008/ES, CLP.

15.2 Chemical safety assessment:

No data available.

SECTION 16: Other information

Reason for alteration:

25.11.2019 - replacement of toluene with xylene.

Key or legend to abbreviations and acronyms used in the safety data sheet:

Flam Gas 1	flammable gas, cat. 1
Press. Gas (liq.)	gas under pressure (liquefied)
Flam. Liq. 3	flammable liquid, cat. 3
Flam. Liq. 2	flammable liquid, cat. 2
Asp. Tox. 1	aspiration hazard, cat. 1
Aerosol 1	highly flammable aerosol
STOT SE 3	specific target organ toxicity after single exposure, cat. 3
Aquatic Chronic 3	long-term aquatic hazard, cat. 3
Aquatic Chronic 2	long-term aquatic hazard, cat. 2
Skin Sens. 1	skin sensitization, cat. 1, cat. 2
Skin Irrit. 2	irritating for skin, cat. 2
Eye Irrit. 2	irritating for eyes, cat. 2
Acute Tox. 4	acute toxicity, cat. 4
STOT RE 2	specific target organ toxicity after repeated exposure, cat. 2

SAFETY DATA SHEET

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 05. 06. 2018 Product code: AP7100

Revision: 25. 11. 2019

Replaced version: 05. 06. 2018

Page: 11 z 12

Trade Name: **PP PLASTIC PRIMER**

NOEC	No Observed Effect Concentration
PBT	Persistent, bioaccumulative, toxic chemical
vPvB	Very Persistent and Very Bioaccumulative chemical
DNEL	Derived No Effect Level
PNEC	Predicted No Effect Concentration
CLP	regulation No. 1272/2008/EC
REACH	regulation No. 1907/2006/EC
bw	body weight

Sources of key data used to compile the Safety Data Sheet:

Chemical databases and tables, tests.

List of H-phrases:

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H226	Flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H220	Extremely flammable gas.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H312+H332	Harmful in contact with skin or if inhaled.
H317	May cause an allergic skin reaction..
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition
P403	Store in a well-ventilated place.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear protective gloves/protective clothing/eye protection.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501	Dispose of contents/container at the site of hazardous waste collection in the village.

Training advice:

SAFETY DATA SHEET

according to Regulation No 1907/2006 of the European Parliament and of the Council

Date of compilation: 05. 06. 2018 Product code: AP7100

Revision: 25. 11. 2019

Replaced version: 05. 06. 2018

Page: 12 z 12

Trade Name: **PP PLASTIC PRIMER**

According to MSDS.

Relevant information for classification:

According to additional method of CLP. For classification, concentrations stated in Section 3 were recalculated according to clause 1.1.3.7 of Annex I to CLP. Articles 3.10.1.6.3 and 1.3.3. of Annex I to CLP have been used.